



HYSTIC® AC801

Electronic Materials

Solvent-base Acrylic Conformal Coating

Material Description

HYSTIC® AC801 is a single component, clear acrylic conformal coating. The coating is sprayed brush-applied and dip-applied, and air dries tack-free to provide a tough environmental coating. The material provides protection of print circuit boards, electronic components, thick-film circuits and other substrates. It contains fluorescent indicator and is easy to repair.

Typical Application

- Single Component
- Fast Drying
- Fluorescent indicator
- Easy to Repair
- UL94 V-0 Flame Resistance
- Protective coating of electronics and circuits. Resist moisture, water, corrosive gas, chemicals.

Curing Condition

Recommended cure @ 80um

- Tack-free time (min) : 5min @80°C
- Full cure(h): 24h

Contact HB Fuller technical support for additional curing recommendations.

Typical Uncured Properties

Property	Value
Raw material	Modified Acrylic Resin
Color	Clear
Viscosity, cps	40
Specific gravity, g/cm ³	0.80

Typical Cured Properties

Cured under 80°C for 5min

Property	Value
Operating time, °C	-40~120
Elongation, %	20
Hardness, Shore A	60
Film thickness, um	25-100
Volume resistivity, ohm.cm@25°C	3X10 ¹⁵
Dielectric constant, 1MHz	3
Dielectric strength, kV/mm	50

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience, and we believe this information to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

© and ™ are trademarks of H.B. Fuller Company or one of its affiliated entities.



NOTE TO USER: by ordering/receiving product, you accept the **H.B. Fuller General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received this documentation. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims, however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability, or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill, or any indirect or consequential losses arising out of or in connection with product supply. (3) Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence, death, or personal injury caused by negligence, or for breach of any mandatory implied terms unless permitted by law.



Engineering Adhesives

TECHNICAL DATA SHEET

Application Instructions

1. Surface should be free of flux, grease, ionic residue or any other contaminants.
2. Brushing or dipping PCB with adhesive, according to selected application.
3. Cured coatings may be removed by soaking in professional cleaning agent.

Storage Conditions

The product should be stored in a cool, dry area in unopened containers between 8-25°C
Shelf life is 12 months from date of manufacture.

Clean Up

Equipment, brushes, and spillage can be cleaned promptly after use with a mixture of anhydrous isopropyl alcohol and acetone that should be discarded after each use.

Please consult your H.B. Fuller technical representative for additional recommendations.

Health & Safety Precautions

Please see the Material Safety Data Sheet (MSDS) for proper handling and disposal instructions.

Note

The values noted in this data sheet are typical properties only and are not intended to be used as material specifications.
For assistance in writing a material specification please contact H.B. Fuller Company.

Conversions

cP x 1000 = mPa·s x 1000 = Pa·s
(°C x 1.8) + 32 = °F
μm / 25.4 = mil
mm / 25.4 = inches
N x 0.225 = lb
N/mm² x 145 = psi
N/mm x 5.71 = lb/in
MPa x 145 = psi
N·m x 0.738 = lb·ft
N·m x 8.851 = lb·in
N·mm x 0.142 = oz·in
kV/mm x 25.4 = V/mil

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience, and we believe this information to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

© and ™ are trademarks of H.B. Fuller Company or one of its affiliated entities.



NOTE TO USER: by ordering/receiving product, you accept the **H.B. Fuller General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received this documentation. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims, however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability, or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill, or any indirect or consequential losses arising out of or in connection with product supply. (3) Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence, death, or personal injury caused by negligence, or for breach of any mandatory implied terms unless permitted by law.

H.B. Fuller
www.hbfuller.com